This listing of claims will replace all prior versions, listings, of claims in the application:

## **Listing of Claims**:

- 1. (original) A polymer-based ammunition, comprising:
  - a composite material including
- a polymer matrix including at least one thermoplastic elastomeric polymer (TPE) component, and at least one soft elastomeric polymer component;

particles of a sufficiently high specific gravity material that are dispersed in the polymer matrix and present in an amount such that the composite material has a specific gravity of in a range from about 2 to 3 grams per cubic centimeter; and the composite material having a shape of a pre-selected projectile.

- 2. (original) The polymer-based ammunition according to claim 1 wherein the thermoplastic elastomeric polymer (TPE) component comprises a block copolymer having at least one elastomeric block.
- 3. (original) The polymer-based ammunition according to claim 2 wherein the thermoplastic elastomeric polymer (TPE) component is selected from the group consisting of polystyrene-polyisobutylene block copolymers, polystyrene-polybutadiene block copolymers, polystyrene-polyisoprene block copolymers, polystyrene-poly(ethylene-butylene block copolymers, polystyrene-poly(ethylene-propylene) block copolymers, thermoplastic polyolefins (TPOs), and dynamically vulcanized TPVs.
- 4. (currently amended) The polymer-based ammunition according to claim 1, <del>2 or 3</del> wherein the thermoplastic elastomeric polymer (TPE) component has a structure selected from the group consisting of linear, star, arborescent, comb, brush, centipede, hyperbranched, and dendritic.

- 5. (currently amended) The polymer-based ammunition according to claim 1, [[2, 3 or 4]] wherein the elastomeric polymer component is selected from the group consisting of polyisobutylene, polyisobutylene-isoprene copolymers, polyisobutylene-styrene copolymers, polyisobutylene- alkyl styrene copolymers, halogenated polyisobutylene- alkyl styrene terpolymers, polybutadiene, polyisoprene, polyethylene-propylene copolymers, polyethylene-propylene diene terpolymers.
- 6. (currently amended) The polymer-based ammunition according to claim 1, [[2, 3 or 4]] wherein the elastomeric polymer component is polyisobutylene, and wherein the thermoplastic elastomeric polymer (TPE) component is polystyrene-polyisobutylene-polystyrene (SIBS).
- 7. (currently amended) The polymer-based ammunition according to claim 1, [[2, 3 or 4]] wherein the elastomeric polymer component is a polyisobutylene-isoprene copolymer, and wherein the thermoplastic elastomeric polymer (TPE) component is polystyrene-polyisobutylene-polystyrene (SIBS).
- 8. (currently amended) The polymer-based ammunition according to claim 1, <del>2, 3,</del> 4, <del>5, 6 or 7</del> wherein the elastomeric polymer component is present in an amount from about 10% to about 90% by weight of the polymer matrix, and wherein the thermoplastic elastomeric polymer component is present in an amount from about 90 to about 10% by weight of the polymer matrix.
- 9. (currently amended) The polymer-based ammunition according to claim 1,  $\frac{2}{3}$ ,  $\frac{3}{5}$ ,  $\frac{6}{9}$  or 7 wherein the elastomeric polymer component is present in an amount from about 40% to about 60% by weight of the polymer matrix, and wherein the thermoplastic elastomeric polymer component is present in an amount from about 60 to about 40% by weight of the polymer matrix.

- 10. (original) The polymer-based ammunition according to claim 5 wherein the elastomeric polymer component has a structure selected from the group consisting of linear, star, arborescent, comb, brush, centipede, hyperbranched and dendritic.
- 11. (currently amended) The polymer-based ammunition according to claim 1,  $\frac{2}{7}$ ,  $\frac{3}{7}$ ,  $\frac{4}{7}$ , or  $\frac{5}{7}$  wherein the specific gravity of the composite material is at least about 2.44 grams per cubic centimeter.
- 12. (currently amended) The polymer-based ammunition according to claim 1,  $\frac{2}{7}$ ,  $\frac{3}{7}$ ,  $\frac{3}{7}$ ,  $\frac{9}{7}$ ,  $\frac{9}{7}$ ,  $\frac{10}{9}$  or  $\frac{11}{7}$  wherein the high specific gravity material is present in the composite material in an amount of from about 50 to about 90% by volume of the total composite.
- 13. (currently amended) The polymer-based ammunition according to claim 1,  $\frac{2}{7}$ ,  $\frac{3}{7}$ ,  $\frac{3}{7}$ ,  $\frac{3}{8}$ ,  $\frac{9}{7}$ ,  $\frac{10}{9}$  or  $\frac{11}{9}$  wherein the high specific gravity material is present in the composite material in an amount of from about 60 to about 80% by volume of the total composite.
- 14. (currently amended) The polymer-based ammunition according to claim 1,  $\frac{2}{7}$ ,  $\frac{3}{7}$ ,  $\frac{4}{7}$ ,  $\frac{5}{7}$ ,  $\frac{6}{7}$ ,  $\frac{7}{8}$ ,  $\frac{9}{7}$ ,  $\frac{10}{9}$  or  $\frac{11}{9}$  wherein the high specific gravity material is present in the composite material in an amount of from about 10 to about 90% by volume of the total composite.
- 15. (currently amended) The polymer-based ammunition according to any one of claims 1 to [[4]] claim 1 wherein the composite material has a cylindrical or spherical shape.
- 16. (currently amended) The polymer-based ammunition according to <del>any one of claims 1 to 15</del> <u>claim 1</u> having a hardness value, as measured according to the Shore A scale, in a range of from about 15 to about 80.

- 17. (currently amended) The polymer-based ammunition according to any one of claims 1 to 15 claim 1 having a hardness value, as measured according to the Shore A scale, in a range of from about 30 to about 55.
- 18. (currently amended) The polymer-based ammunition according to any one of claims 1 to 17 claim 1 wherein the particles of a high specific gravity material are selected from the group consisting of iron powder, tungsten, copper, bismuth, and iron oxide.
- 19. (currently amended) The polymer-based ammunition according to any one of claims 1 to 17 claim 1 wherein the particles of a high specific gravity material are iron powder particles.
- 20. (original) The polymer-based ammunition according to claim 19 wherein the iron powder particles have sizes in a range from about 71.4% of -100 to +325 U.S. Mesh and 23.2% of -325 U.S. Mesh, specific gravity, 7.8 gcm<sup>-3</sup>.
- 21. (currently amended) The polymer-based ammunition according to any one of claims 1 to 20 claim 1 produced by molding the composite material into any one of a cylindrical or spherical shape.
- 22. (original) The polymer-based ammunition according to claim 21 wherein the step of molding is one of injection molding and compression molding.
- 23. (currently amended) The polymer-based ammunition according to any one of claims 1 to 22 claim 1 wherein the composite material has a dynamic mechanical compression creep below a threshold creep so that the polymer-based ammunition maintains its shape.
- 24. (original) The polymer-based ammunition according to any one of claim 23 wherein said threshold dynamic mechanical compression creep is about 20%.

- 25. (original) The polymer-based ammunition according to claim 23 wherein dimensions of the composite material do not change more than 10% for at least a year.
- 26. (currently amended) The polymer-based ammunition according to any one of claims 1 to 23 claim 1 wherein the composite material has a dynamic mechanical compression creep between 4 and 20% creep.
- 27. (original) A composite material, comprising:

a polymer matrix including at least one thermoplastic elastomeric polymer (TPE) component, and at least one soft elastomeric polymer component, the thermoplastic elastomeric polymer (TPE) component including a block copolymer having at least one elastomeric block, the material characterized in that it exhibits a dynamic mechanical compression creep below a threshold creep so that the composite material maintains its shape.

- 28. (original) The polymer-based ammunition according to claim 27 wherein the thermoplastic elastomeric polymer (TPE) component is selected from the group consisting of polystyrene-polyisobutylene block copolymers, polystyrene-polybutadiene block copolymers, polystyrene-polyisoprene block copolymers, polystyrene-poly(ethylene-butylene block copolymers, polystyrene-poly(ethylene-propylene) block copolymers, thermoplastic polyolefins (TPOs), and dynamically vulcanized TPVs.
- 29. (currently amended) The composite material according to claim 27 or 28 wherein the elastomeric polymer component is selected from the group consisting of polyisobutylene, polyisobutylene-isoprene copolymers, polyisobutylene-styrene copolymers, polyisobutylene- alkyl styrene copolymers, halogenated polyisobutylene- alkyl styrene terpolymers, polybutadiene, polyisoprene, polyethylene-propylene copolymers, polyethylene-propylene diene terpolymers.

- 30. (currently amended) The composite material according to claim 27, <del>28 or 28</del> wherein the thermoplastic elastomeric polymer (TPE) component and the elastomeric polymer component have a structure selected from the group consisting of linear, star, arborescent, comb, brush, centipede, hyperbranched, and dendritic.
- 31. (currently amended) The composite material according to claim 27, 28, 29 or 30 including particles of a high specific gravity material that are dispersed in the polymer matrix and present in an amount such that the composite material has a specific gravity of in a range from about 2 to 3 grams per cubic centimeter.
- 32. (original) The composite material according to claim 31 wherein the particles of a high specific gravity material are selected from the group consisting of iron powder, tungsten, copper, bismuth, and iron oxide.
- 33. (original) The composite material according to claim 31 wherein the particles of a high specific gravity material are iron powder particles.
- 34. (currently amended) The composite material according to claim 26, 27, 28, 29, 30, 31, 32 or 33 claim 27 wherein the elastomeric polymer component is one of polyisobutylene and polyisobutylene-isoprene copolymer.
- 35. (currently amended) The polymer-based ammunition according to any one of claims 26 to 33 claim 27 wherein said threshold dynamic mechanical compression creep is about 20%.
- 36. (currently amended) The polymer-based ammunition according to any one of claims 26 to 35 claim 27 wherein the composite material has a dynamic mechanical compression creep between 4% and 20% creep.
- 37. (currently amended) The polymer-based ammunition according to any one of claims 27 to 34 claim 27 wherein dimensions of the composite material do not change more than 10% for at least a year.